



larger image

Results 1 - 9 of 9

<u>Item #</u>	<u>Item Name</u>	<u>Viscosity</u>	<u>Color</u>	<u>Specific Gravity</u>	<u>Tensile Strength</u>	<u>Temp. Range</u>	<u>Gap Fill (inches)</u>	<u>MSDS</u>	<u>TDS</u>
<u>MP 53020</u>	MP 5300 Series	2200 cps	Clear	1.10	3800 psi	-60 to 350 ° F	0.010	<u>MSDS</u>	<u>TDS</u>
<u>MP 53021</u>	MP 5300 Series	750 cps	Clear	1.00	4200 psi	-60 to 350 ° F	0.008	<u>MSDS</u>	<u>TDS</u>
<u>MP 53022</u>	MP 5300 Series	6000 cps	Clear	1.10	3800 psi	-60 to 375 ° F	0.015	<u>MSDS</u>	<u>TDS</u>
<u>MP 53023</u>	MP 5300 Series	100 cps	Clear	1.10	4200 psi	-60 to 350 ° F	0.006	<u>MSDS</u>	<u>TDS</u>
<u>MP 53024</u>	MP 5300 Series	3200 cps	Clear	1.10	4000 psi	-60 to 375 ° F	0.010	<u>MSDS</u>	<u>TDS</u>
<u>MP 53037</u>	MP 5300 Series	2500 cps	Clear	1.10	3200 psi	-60 to 375 ° F	0.010	<u>MSDS</u>	<u>TDS</u>
<u>MP 53301</u>	MP 5300 Series	200 cps	Clear	1.10	4000 psi	-60 to 350 ° F	0.006	<u>MSDS</u>	<u>TDS</u>
<u>MP 53344</u>	MP 5300 Series	2500 cps	Clear	1.10	3000 psi	-60 to 275 ° F	0.010	<u>MSDS</u>	<u>TDS</u>
<u>MP 53347</u>	MP 5300 Series	8000 cps	Clear	1.12	3000 psi	-60 to 275 ° F	0.020	<u>MSDS</u>	<u>TDS</u>