


Torque Threadsealers

Check up to five results to perform an action.

Anaerobic Adhesives/Sealants Threadsealing

The TORQUE liquid thread sealants are specifically designed to seal and secure metal pipes and fittings by filling the space between threaded metal parts and hardening to prevent leakage. They do an excellent job of sealing in severe environmental conditions and prevent leakage that may be caused by vibration loosening, damaged threads, or temperature cycling. TORQUE liquid thread sealants seal instantly to moderate pressures and when fully cured; they seal to the burst strength of most piping systems. They have excellent resistance to a wide range of chemicals such as hydraulic fluids, oils, fuels, water, lubricants, etc. They are ready to use, single component, solvent free materials, designed to handle both low and high pressure applications. The TORQUE THREADSEALING products do not shrink, shred, tear, or relax. They are formed in place sealants conforming to the parts they are used on, creating a durable, positive seal. The TORQUE THREADSEALING family of products offers a full range of viscosities, strengths, and cure speeds that are designed to meet your specific application requirements.



larger image

Results 1 - 17 of 17

1

| <u>Item #</u> | <u>Item Name</u> | <u>Color</u> | <u>Viscosity</u> | <u>Temp. Range</u> | <u>Cure Speed (Fixture)</u> | <u>Cure Speed (Full)</u> | <u>Specific Gravity</u> | <u>MSDS</u> | <u>TDS</u> |
|-------------------|----------------------|--------------|------------------|--------------------|-----------------------------|--------------------------|-------------------------|-------------|------------|
| <u>TORQUE 145</u> | Torque Threadsealers | Purple | 10000 cps | -60 to 350 °F | 15 min. | 8 hours | 1.20 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 154</u> | Torque Threadsealers | Red | 2500 cps | -60 to 350 °F | 10 min. | 8 hours | 1.02 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 165</u> | Torque Threadsealers | White | 300000 cps | -60 to 350 °F | 10 min. | 8 hours | 1.10 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 170</u> | Torque Threadsealers | Blue | 4500 cps | -60 to 400 °F | 10 min. | 8 hours | 1.12 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 171</u> | Torque Threadsealers | White | 40000 cps | -60 to 350 °F | 5 min. | 8 hours | 1.08 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 172</u> | Torque Threadsealers | Blue | 750 cps | -60 to 350 °F | 15 min. | 8 hours | 1.05 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 173</u> | Torque Threadsealers | Brown | 500 cps | -60 to 350 °F | 10 min. | 8 hours | 1.06 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 174</u> | Torque Threadsealers | Red | 3500 cps | -60 to 350 °F | 10 min. | 8 hours | 1.08 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 175</u> | Torque Threadsealers | Red | 4000 cps | -60 to 350 °F | 10 min. | 8 hours | 1.08 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 176</u> | Torque Threadsealers | Blue | 20000 cps | -60 to 350 °F | 10 min. | 8 hours | 1.09 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 177</u> | Torque Threadsealers | White | 90000 cps | -60 to 350 °F | 5 min. | 6 hours | 1.09 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 178</u> | Torque Threadsealers | Yellow | 50000 cps | -60 to 350 °F | 10 min. | 8 hours | 1.09 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 180</u> | Torque Threadsealers | Green | 500 cps | -60 to 350 °F | 2 min. | 6 hours | 1.06 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE 181</u> | Torque Threadsealers | Green | 3500 cps | -60 to 450 °F | 15 min. | 8 hours | 1.10 | <u>MSDS</u> | <u>TDS</u> |
| <u>TORQUE</u> | Torque | | | -60 to | | | | <u>MSDS</u> | <u>TDS</u> |