



Applications where FEP tubing is chosen usually require more clarity, flexibility or a lower heat shrinkable temperature than PTFE.

Inside Diameter (inches)				Wall Dimensions (inches)							Packaging
AWG Size	Min.	Nom.	Max	Standard Wall		Thin Wall		Light weight wall			
				Nom.	Tol.	Nom.	Tol.	Nom.	Tol.		
32	0.008	0.010	0.012	0.005	+/- .002	0.005	+/- .002	-	-	1000' Spools	
30	0.010	0.012	0.015	0.009	+/- .002	0.009	+/- .002	0.006	+/- .002	1000' Spools	
28	0.013	0.015	0.018	0.009	+/- .002	0.009	+/- .002	0.006	+/- .002	1000' Spools	
26	0.016	0.018	0.021	0.009	+/- .002	0.009	+/- .002	0.006	+/- .002	1000' Spools	
24	0.020	0.022	0.026	0.012	+/- .002	0.010	+/- .003	0.006	+/- .002	1000' Spools	
23	0.023	0.026	0.029	0.012	+/- .002	0.010	+/- .003	0.006	+/- .002	1000' Spools	
22	0.026	0.028	0.032	0.012	+/- .002	0.010	+/- .003	0.006	+/- .002	1000' Spools	
21	0.029	0.032	0.035	0.012	+/- .002	0.010	+/- .003	0.006	+/- .002	1000' Spools	
20	0.032	0.034	0.038	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools	
19	0.036	0.038	0.042	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools	
18	0.040	0.042	0.046	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools	
17	0.045	0.047	0.052	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools	
16	0.051	0.053	0.058	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools	

15	0.057	0.059	0.065	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools
14	0.064	0.066	0.072	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
13	0.072	0.076	0.081	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
12	0.081	0.085	0.091	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
11	0.091	0.095	0.101	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
10	0.102	0.106	0.112	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
9	0.114	0.118	0.124	0.020	+/- .004	0.015	+/- .003	0.008	+/- .002	250' Spools
8	0.129	0.133	0.139	0.020	+/- .004	0.015	+/- .003	0.008	+/- .002	-
7	0.144	0.148	0.155	0.020	+/- .004	0.015	+/- .003	0.008	+/- .003	-
6	0.162	0.166	0.174	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
5	0.182	0.186	0.195	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
4	0.204	0.208	0.218	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
3	0.229	0.234	0.244	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
2	0.258	0.263	0.273	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
1	0.289	0.294	0.294	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
0	0.325	0.330	0.342	0.020	+/- .004	0.015	+/- .003	0.012	+/- .003	-